VersiTape[®] F100 Self-Adhesive Butyl Tape with Fleece





We make the difference. The Elmich Difference.

VersiTape[®] F100

VersiTape® F100 is a self-adhesive sealing tape comprising a butyl rubber compound and polypropylene fleece. VersiTape® F100 has excellent adhesion and stability at high and low temperatures, and its plasticity enables it to conform to edges.

VersiTape® F100 is used in place of traditional cement fillets as reinforcement for waterproofing membrane application at wall/floor junctions. Compared to cement fillets, application of the preformed VersiTape® F100 is more efficient and its pre-determined uniform thickness ensures high structural integrity as a reinforcement.



Technical Specifications

Oleane stanistics	Malaa	T 4
Characteristics	Value	Test
Standard thickness	1.0 mm	-
Compound colour	Grey	-
Tensile strength	>150 N/50 mm	EN 12311-1
Elongation at break	>70%	EN 12311-1
Solids	100%	-
Specific weight	1.4 g/cm ³	ASTM D 792
Peel adhesion 90°	≥90 N	ASTM D 1000
Loop tack test	≥80 N	ASTM D 6195
Probe tack test	≥80 N	ASTM D 2979

© Elmich Pte Ltd VTF/001-V1-0320SG



Note The information provided in this brochure is based on current knowledge and experience and does not infer any legally binding assurance or warranty, expressed or implied. Intending purchasers should verify whether any changes to specifications or applications or otherwise have been made since the issue of this literature. Environmentally-friendly recycled materials are used in product manufacture wherever possible. Physical product properties including colour may differ due to source of raw materials used. Colour may also fade due to UV exposure. All components of the product are designed for specific application, design calculations and any variation and/or deviation therefrom shall be the responsibility of the specifier and/or user.



Elmich Pte Ltd (65) 6356 2800

info@elmich.com

Singapore • Australia • Malaysia

Switzerland • Germany • USA

t

е