

Euraflex™ is a high-performance EPDM rubber liner that is suitable for various applications such as ponds, water features, and even concealed pitched roofs. Its high flexibility allows it to conform to various degrees of slopes and edges. Additionally, it boasts of a high durability regardless of weather conditions, thus allowing it to achieve a long service life.



Technical Specifications

Dimensions	2 m x 20 m	Test Method	Value
Thickness	1.2 mm		
Dynamic puncture resistance	ASTM D4637	Pass	
Static puncture resistance	ASTM D4637	Pass	
Water absorption	ASTM D4637	Pass	
Ozone resistance	ASTM D4637	Pass	
Tear resistance	ASTM D4637	Pass	
Tensile test	ASTM D4637	Pass	
Thickness	ASTM D4637	Pass	
Brittleness point	ASTM D4637	Pass	
Dark oven heat exposure	ASTM D4637	Pass	



Elmich Pte Ltd

t +65 6356 2800

e info@elmich.com

Singapore • Australia • Malaysia
Switzerland • Germany • USA

Note The information provided in this brochure is based on current knowledge and experience and does not infer any legally binding assurance or warranty, expressed or implied. Intending purchasers should verify whether any changes to specifications or applications or otherwise have been made since the issue of this literature. Environmentally-friendly recycled materials are used in product manufacture wherever possible. Physical product properties including colour may differ due to source of raw materials used. Colour may also fade due to UV exposure. All components of the product are designed for specific application, design calculations and any variation and/or deviation therefrom shall be the responsibility of the specifier and/or user.